

FIRECHIEF XTR STEEL ALLOY CO₂ EXTINGUISHERS

FIRECHIEF[®]
making the world a safer place

MODEL:

FXCD2S
FXCD5S



FXCD2S
100-1393

FXCD5S
100-1392

- Kitemarked and LPCB approved to BS EN3
- MED approved
- 5 year guarantee
- Designed, developed and tested in UK
- Lightweight steel alloy construction
- Squeeze grip operation
- Harmless to machinery
- Complete with bracket
- Corrosion resistant finish
- FXCD2S supplied with frost free horn



+44 (0) 330 999 0019



sales@firechiefglobal.com



firechiefglobal.com

FIRECHIEF XTR STEEL ALLOY CO2 EXTINGUISHERS

FIRECHIEF®
making the world a safer place

This lightweight steel alloy CO2 extinguishers are suitable for situations involving flammable liquids and electrical hazards. One of the best selling extinguishers in the Firechief XTR range, the CO2 extinguishant is harmless to delicate equipment and materials making it ideal for office environments and for electrical risks where oils, spirits etc are in use.

**MODEL:
FXCD2S
FXCD5S**



Specifications

Model	FXCD2S	FXCD5S
Product Code	100-1393	100-1392
Description	Firechief XTR 2kg CO2 Extinguisher - Steel	Firechief XTR 5kg CO2 Extinguisher - Steel
Capacity (kg)	2kg	5kg
Fire Rating	34B	70B
MED Approval	Yes	Yes
Throw Range (m)	2	2.5
Discharge Time (secs)	8	13
Working Pressure (bar)	56	56
Temperature Range (°C)	-30°C-+60°C	-30°C-+60°C
Product Height (mm)	580	745
Product Diameter (mm)	103	136
Filled Weight (kg)*	6.2	13.3
Carton Height (mm)	600	770
Carton Length (mm)	155	210
Carton Width (mm)	125	150
Packaged Weight (kg)**	6.5	14
Pallet Quantity	84	40
Product EAN	5055377900441	5055377900458

* Extinguisher, contents and plastic base only (where applicable) - not including hose, bracket or packaging.

** Includes all packaging, hose / horn and bracket.

For more information contact: Firechief Global, 3 Lands End Way, Oakham, Rutland, UK, LE15 6RB | Imported into EU by: Sentura Group (Ireland) Ltd, Joyce House, 21-23 Holles Street, Dublin 2, Ireland

 +44 (0) 330 999 0019

 sales@firechiefglobal.com

 firechiefglobal.com